

DOVE STEEL LLC

Stainless Steel Flat Rolled Products

Stainless Steel HR Coil			
Product Specification and Sizes			
Width	Thickness	Grades	Finish
39.37" to 64.96"	0.079" to 0.472"	200 Series - 201, 201L, 201LN, 202 300 Series - 301, 301L, 301LN, 304, 304H, 304L, 304LN, 309S, 310, 316, 316L, 316LN, 316Ti, 317, 317L, 317LN, 321, 347 400 Series - 405, 409, 410, 410S, 420, 430, 431, 436, 436L, 439 Duplex - 2205, 2304	HR, No. 1, 2E

Stainless Steel CR Coil			
Width	Thickness	Grades	Finish
39.37" to 63.00"	0.012" to 0.197"	Same as above	2B, 2D, BA, No.4 (with Paper/PVC)

Slitting Capabilities	
Hot Rolled Coil/Strip	0.630" min width
Cold Rolled Coil/Strip	0.197" min width

Thickness	Min Slit Width
Up to 0.031"	0.197" CR
0.035 to 0.079"	0.394" CR
0.079 to 0.118"	0.630" CR-HR
0.118" and above	0.787" CR-HR

Stainless Steel Plates			
Width	Thickness	Grades	Finish
39.37" to 64.78" Length: CTL up to 236"	0.236" to 3.150"	Same as above	No.1

Stainless Steel Sheets			
Width	Thickness	Grades	Finish
39.37" to 63.00" Length: CTL up to 236"	0.012" to 0.197"	Same as above	2B, BA, No.4, No.8